

| Ref # | Hits  | Search Query   | DBs   | Default Operator | Plurals | Time Stamp       |
|-------|-------|--|---|------------------|---------|------------------|
| L1    | 12841 | (introducer or sheath or cannula or tube or tubular or shaft or catheter) with (pressure with sensor)  | US-PGPUB;<br>USPAT;<br>USOCR;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR               | OFF     | 2006/01/31 13:44 |
| L2    | 982   | 1 and ((core with pin) or (inner with (lumen or path or channel or groove or slot)))   | US-PGPUB;<br>USPAT;<br>USOCR;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR               | OFF     | 2006/01/31 13:45 |
| L3    | 356   | 2 and ((side or lateral\$4) with (port or opening or hole or aperture))  | US-PGPUB;<br>USPAT;<br>USOCR;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR               | OFF     | 2006/01/31 13:46 |
| L4    | 0     | system and (introducer with assmbly) and (pressure with sensor) and (blood with pressure) and (pressure with distal) and (core with (pin or mandril or mandrel)) and ((side or lateral\$4) with (hole or opening or aperture or inlet or port)).clm. | US-PGPUB;<br>USPAT;<br>USOCR;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR               | ON      | 2006/01/31 13:49 |